































ردیف	مدل	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
IP Camera - IR				
1	SM-IP8414M-W 	1/2.8" SONY CMOS Sensor 8MP(20FPS)/3.6 mm fixed Lens/3Stream/H.265+/H.264+ True WDR 120dB /50m IR/0.1 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions		Hyperlink 98,750,000
2	SM-IP8512M-W 	1/2.8" SONY CMOS Sensor 8MP(20FPS)/2.8 mm fixed Lens/3Stream/H.265+/H.264+ True WDR 120dB /30m IR/0.06 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input and 1CH built-in MIC/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions		Hyperlink 93,750,000
3	SM-IP5512HM-W	1/2.7" CMOS Sensor 5MP(20FPS)/2.8 mm fixed Lens /3Streams/H265+/H264+/ True WDR 120DB /30m IR/0.007 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions		Hyperlink 50,000,000
4	SM-IP4412HM-W	1/3" CMOS Sensor 4MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+/ True WDR 120DB/30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions		Hyperlink 43,750,000
5	SM-IP4512HM-W	1/3" CMOS Sensor 4MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+/ True WDR 120DB /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions		Hyperlink 43,750,000
6	SM-IP2412HM-WS	1/2.8" CMOS Sensor 2MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB /Starlight /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB/ ONVIF/IP67 Metal SMART Functions		Hyperlink 40,750,000
7	SM-IP2512HM-WS	1/2.8" CMOS Sensor 2MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB /Starlight /30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions		Hyperlink 40,750,000
8	SM-IPTZ-2MP-15X/MS	1/2.8" progressive scan CMOS, BSI, NIR+ / 2MP(25FPS) 5 - 75 mm Motorized Lens/15x Optical Zoom/200m SMART IR/H.265+, H.264+/DWDR /Starlight SD Card Max 256GB/IP66, IK10 Metal /DC12V 3A, PoE SMART Functions/ Auto Tracking		Hyperlink 4inch 207,500,000













9	SM-IPTZ-4MP-4X/MWSFR	1/2.7" progressive scan CMOS with BSI and NIR+ technology Sensor 4MP(25FPS) / 2.8-12mm Motorized Lens/4x Optical Zoom/50m IR/H.265+,H.264+/ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/built-in Mics & Speaker (8m for voice recording, 30m for audible warnings)/ 1 Ch input ,1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC12V 2A, PoE+ SMART Functions/ Auto Tracking/ Supports face detection and comparison/ Active Deterrence (30m White LED)	    	Hyperlink 170,000,000
10	SM-IPTZ-4MP-4X/MWS	1/2.7" progressive scan CMOS with BSI and NIR+ technology Sensor 4MP(25FPS) / 2.8-12mm Motorized Lens/4x Optical Zoom/50m IR/H.265+,H.264+/ True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/built-in Mics & Speaker (8m for voice recording, 30m for audible warnings)/ 1 Ch input ,1 Ch output Alarm/SD Card Max 256GB/IP66, IK10 Metal/Outdoor/ DC12V 2A, PoE+ SMART Functions/ Auto Tracking/ Active Deterrence (30m White LED)	   	Hyperlink 147,500,000
11	SM-IPTZ-4MP-40X/MSFD	1/2.8" progressive scan CMOS Sensor, BSI and NIR++, dual gain, 4MP(25FPS) / 4.5 ~ 180 mm Motorized Lens/40x Optical Zoom/350m Smart IR/H.265+,H.264+/DWDR/Starlight 1 Ch input, 1 Ch output Audio/1 Ch input ,1 Ch output Alarm/SD Card Max 256GB/IP67, IK10 Metal/Outdoor/ DC24V 1.5A ,PoE++ SMART Functions/ Auto Tracking/ Supports face detection/ target counting	   	Hyperlink 475,000,000
















































IP Camera - Color View

12	SM-IP4512CV2-W	1/3" CMOS Sensor 4MP(25FPS) / 2.8mm fixed Lens/3Streams/H265/ H264/ True WDR 120dB/20~ 30m white light view distance/0.003 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions	   	Hyperlink 51,250,000
13	SM-IP2414CV2-W	1/2.8" CMOS Sensor 2MP(25FPS) / 3.6mm & 2.8 mm fixed Lens/3Streams/H265+/ H264+/ True WDR 120dB/30~ 40m white light view distance/0.002 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions	   	Hyperlink 53,750,000
14	SM-IP2512CV2-W	1/2.8" CMOS Sensor 2MP(25FPS) / 2.8 mm fixed Lens/3Streams/H265+/ H264+/ True WDR 120dB/20~ 30m white light view distance/0.002 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1CH audio input; 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions	   	Hyperlink 47,500,000





IP Camera - Dual Light

15	NEW SM-IPN6412DM-WS	1/2.5" CMOS Sensor 6MP(20FPS) /3.6mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB/Starlight/0.008 Lux/ ICR , Auto day/night switch 30m White light view distance; 30m IR view distance ROI coding, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	     	Hyperlink 58,750,000
16	NEW SM-IPN6512DM-WS	1/2.5" CMOS Sensor 6MP(20FPS) /2.8mm fixed Lens/3Streams/H265+/H264+/ True WDR 120dB/Starlight/0.008 Lux/ ICR , Auto day/night switch 30m White light view distance; 30m IR view distance ROI coding, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	     	Hyperlink 58,750,000

17	SM-IPN4410DL	1/3" CMOS Sensor 4MP(25FPS)/3.6mm fixed Lens/2Streams/H265+/H264+/ DWDR /0.09 Lux/ ICR , Auto day/night switch 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH built-in MIC/ONVIF/IP67(Metal&Plastic) SMART Functions-Support SMD (available for human)	   	Hyperlink 33,250,000
18	SM-IPN4510DL	1/3" CMOS Sensor 4MP(25FPS)/2.8mm fixed Lens/2Streams/H265+/H264+/ DWDR /0.09 Lux/ ICR , Auto day/night switch 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH built-in MIC/ONVIF/IP67(Metal&Plastic) SMART Functions-Support SMD (available for human)	   	Hyperlink 33,250,000
19	NEW SM-IPN2416DM-VFWS	1/2.8" CMOS Sensor 2MP(25FPS)/2.8 -12mm Motorized Varifocal Lens/3Streams/H265+/H264+/ True WDR 120dB/Starlight/0.006 Lux/ ICR , Auto day/night switch 40m White light view distance; 50m IR view distance ROI coding, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	     	Hyperlink 58,000,000
20	NEW SM-IPN2516DM-VFWS	1/2.8" CMOS Sensor 2MP(25FPS)/2.8 -12mm Motorized Varifocal Lens/3Streams/H265+/H264+/ True WDR 120dB/Starlight/0.006 Lux/ ICR , Auto day/night switch 40m White light view distance; 50m IR view distance ROI coding, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH audio input/1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67(Metal) SMART Functions-Support SMD (human / Motor Vehicle)	     	Hyperlink 57,250,000
21	SM-IPN2410DL	1/3" CMOS Sensor 2MP(25FPS)/3.6mm fixed Lens/2Streams/H265+/H264+/ DWDR/0.02 Lux/ ICR , Auto day/night switch 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH built-in MIC/ONVIF/IP67(Metal&Plastic) SMART Functions-Support SMD (available for human)	   	Hyperlink 26,600,000
22	SM-IPN2510DL	1/3" CMOS Sensor 2MP(25FPS)/2.8mm fixed Lens/2Streams/H265+/H264+/ DWDR /0.02 Lux/ ICR , Auto day/night switch 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Smart IR POE/12VDC/1CH built-in MIC/ONVIF/IP67(Metal&Plastic) SMART Functions-Support SMD (available for human)	   	Hyperlink 26,600,000
23	NEW SM-IPS2410DL	1/3" CMOS Sensor 2MP(25FPS)/3.6mm fixed Lens/2Streams/H265+/H264+/ DWDR/0.0462 Lux/ ICR , Auto day/night switch Dual light Camera (line Crossing-Intrusion) 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR POE/1CH built-in MIC/ONVIF/IP67(Metal&Plastic) SMART Functions	   	Hyperlink 18,500,000
24	NEW SM-IPS2510DL	1/3" CMOS Sensor 2MP(25FPS)/2.8mm fixed Lens/2Streams/H265+/H264+/ DWDR/0.0462 Lux/ ICR , Auto day/night switch Dual light Camera (line Crossing-Intrusion) 20m White light view distance; 20m IR view distance ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR POE/1CH built-in MIC/ONVIF/IP67(Metal&Plastic) SMART Functions	   	Hyperlink 18,500,000
NVR				
25	SM-NLS4016	4CH input & Record 6MP@25fps /H.265S ,H.265+/ Bandwidth(Input 40Mbps/Output 40Mbps) 4CH IPC Audio/Alarm input/SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	Hyperlink 29,250,000
26	SM-NLS4016-4PE	4CH input & Record 6MP@25fps - 4*100M RJ45 PoE ports H.265S ,H.265+ -Bandwidth(Input 40Mbps/Output 40Mbps) 4CH IPC Audio input/SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	Hyperlink 47,500,000

27	SM-NLS8016	8CH input & Record 6MP@25fps /H.265S ,H.265+/ Bandwidth(Input 64Mbps/Output 64Mbps) 8CH IPC Audio/Alarm input/ SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/ P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 VCA 	Hyperlink 33,400,000
28	SM-NLS1616	16CH input & Record 6MP@25fps /H.265S ,H.265+/ Bandwidth(Input 64Mbps/Output 64Mbps) 16CH IPC Audio/Alarm input/ SATA3.0 x 1, max 10T / HDMI-VGA/USB2.0*2/ P2P/ ONVIF/DHCP/DDNS/ RJ45 100Mbps x 1 SMART Function/Supports face detection/Video Metadata/Perimeter Protection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 VCA 	Hyperlink 38,000,000
29	SM-N2M1618	16CH input & Record 8MP(25FPS)/H.265S ,H.265+/ Bandwidth (Input160Mbps/Output 160Mbps) 16CH IPC Audio/Alarm input/ SATA3.0 x 1, max 10T/ HDMI 4K-VGA/ 2 RCA AUDIO IN & OUT/ USB2.0*2 / P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M SMART Function/Supports face detection/Video Metadata/Perimeter Protection/Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 VCA 	Hyperlink 61,000,000
30	SM-N2M1628	16CH input & Record 8MP(25FPS)/H.265S ,H.265+/ Bandwidth (Input160Mbps/Output 160Mbps) 16CH IPC Audio/Alarm input/4 CH local alarm input- 1Ch Output/ SATA3.0 x 2, max 10T per HDD/HDMI 4K-VGA 2 RCA AUDIO IN & OUT/ RS485*2/ USB2.0*2 / P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M SMART Function/Supports face detection/Video Metadata/Perimeter Protection/Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 VCA 	Hyperlink 78,000,000

SWITCH

31	SM-LC41P	5 Ports / 4x10/100/1000M POE + 1 Gigabit uplink IEEE802.3af/at , built-in power / TOTAL 72W long distance 250m		Hyperlink 18,000,000
32	SM-LB82P	10 Ports / 8x10/100M POE + 2 Gigabit uplink IEEE802.3af/at , built-in power / TOTAL 120W long distance 250m		Hyperlink 23,000,000
33	SM-LC82P-SF	10 Ports / 8x10/100/1000M POE + 2 Gigabit uplink & 1SFP port(1000Mbps) IEEE802.3af/at , built-in power / TOTAL 120W long distance 250m		Hyperlink 30,000,000
34	SM-LB162P-SF	18 Ports / 16x10/100M POE + 2 Gigabit uplink & 1SFP port(1000Mbps) IEEE802.3af/at , built-in power / TOTAL 300W * 1 long distance 250m		Hyperlink 62,500,000

کلیه محصولات لیست با گارانتی شرکت سیماران می باشند