


ردیف	سیماران	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
Low level-IR				
1	SM-D721IRV	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens / 0.1LUX/24PCS IR-20~30m 12 VDC/ICR/DWDR, 3-DNR, BLC,D&N,AGC, UTC Function, Metal IP66		5,600,000
2	SM-D722IR	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens / 0.1LUX/18PCS SMD IR-20~30m 12 VDC/ICR/DWDR, 3-DNR, BLC,D&N,AGC, UTC Function, Plastic		4,700,000
3	SM-IR719	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens / 0.1LUX/18PCS SMD IR-20~30m 12 VDC/ICR/DWDR, 3-DNR, BLC,D&N,AGC, UTC Function, Plastic		4,850,000
4	SM-IR728	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens/ 0.1LUX/18PCS SMD IR-20~30m 12 VDC/ICR/DWDR, 3-DNR, BLC,D&N,AGC, UTC Function, Metal IP66		6,190,000
5	SM-IR729	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens / 0.1LUX/18PCS SMD IR-20~30m 12 VDC/ICR/DWDR, 3-DNR, BLC,D&N,AGC, UTC Function, Metal IP66		5,700,000
6	SM-IR747	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens/ 0.1LUX/24PCS SMD IR-35~40m 12 VDC/ICR/DWDR, 3-DNR, BLC,D&N,AGC, UTC Function, Metal IP66		6,500,000
7	SM-AR752	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens/ 0.1LUX/4 pcs Array IR-60~65m 12 VDC/ICR/DWDR, 3-DNR, BLC,D&N,AGC, UTC Function, Metal IP66		7,690,000
High level-IR				
8	SM-AR512M	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI /3.6mm Fixed lens/ 0.01LUX/20~30m IR 12 VDC/ICR/COC/DWDR, 2DNR,AGC,BLC,AWB,D&N,Sharpness, IP67(Metal&Plastic)		10,750,000
9	SM-D511MV	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI /3.6mm Fixed lens/ 0 lux with IR/ 20~30m IR 12 VDC/ICR/COC/ 2DNR,BLC,AWB,D&N,Sharpness IP66(Metal&Plastic)		10,500,000
10	SM-AR216M	1/2.7" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 2.8mm Fixed lens/ 0 lux (IR ON)/ 50~55m IR 12 VDC/ICR/COC/DWDR, 2DNR,AGC,BLC,AWB,D&N,Sharpness,Smart IR, IP66(Metal&Plastic)		8,812,500
11	SM-AR212M3	1/3" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens/ 0 lux (IR ON)/ 20~30m IR 12 VDC/ICR/COC/DWDR, 3DNR,AGC,BLC,AWB,D&N,Sharpness,Smart IR, IP67(Metal&Plastic)		8,190,000

12	SM-D211M3V	1/3" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 2.8mm Fixed lens/ 0 lux (IR ON)/ 20-30m IR 12 VDC/ICR/COC/DWDR, 3DNR,AGC,BLC,AWB,D&N,Sharpness,Smart IR, IP67(Metal&Plastic)		8,565,000
13	SM-D331IRVR	1/2.9" SONY CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 2.8-12 mm VF lens /0.01LUX/24pcs IR-30-35m/ 12VDC/ICR/D-WDR,Brightness,Sharpness,Shutter, AGC,BLC,D&N,Defog,3DNR,AWB,UTC,Metal IP66		13,750,000
14	SM-IR348VF	1/2.9" SONY CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 2.8-12 mm VF lens /0.01LUX/30pcs IR-40-45m/ 12VDC/ICR/D-WDR,Brightness,Sharpness,Shutter, AGC,BLC,D&N,Defog,3DNR,AWB,UTC,Metal IP66		15,312,500
CV - Warm Light Full Color Camera Light Explorer				
15	SM-AR524MCV	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON)/ 30-35m LED Distance 12 VDC/COC/DWDR, 2DNR,AGC,BLC,AWB,Sharpness,Smart LED, Metal IP67	 Full-Color	13,250,000
16	SM-AR512MCVA	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON) / 20-30m LED Distance Support coaxial audio transmission 12 VDC/COC/DWDR, 2DNR,AGC,BLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)	 Full-Color	12,500,000
17	SM-D523MCVA	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON)/ 30-35m LED Distance Support coaxial audio transmission 12 VDC/COC/DWDR, 2DNR,AGC,BLC,AWB,Sharpness,Smart LED, Metal IP67	 Full-Color	13,500,000
18	SM-AR212MCV	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 20-30m LED Distance 12 VDC/COC/DWDR, 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)	 Full-Color	9,375,000
19	SM-D211MCV	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 20-30m LED Distance 12 VDC/COC/DWDR, 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)	 Full-Color	9,815,000
20	SM-D223MCVA	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 30-35m LED Distance/Support coaxial audio transmission 12 VDC/COC/DWDR, 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, Metal IP67	 Full-Color	12,125,000
21	NEW SM-CV534	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/4pcs -20m white light view distance/ DC12V/COC/DWDR, 2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color	9,100,000
22	SM-CV147	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/8pcs -20-30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66	 Full-Color	7,440,000

23	SM-CV133	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,IP66(Metal&Plastic)		6,325,000
24	SM-CV134	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66		6,940,000
25	SM-CV135	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66		6,775,000
26	SM-CV136	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66		6,800,000
27	SM-CV152	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -30~35m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66		9,725,000
28	SM-CV119	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/6pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Plastic		5,815,000
29	SM-D122CV	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/6pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Plastic		5,500,000
30	SM-D121CV	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/6pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66		6,625,000
31	SM-D120CV	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/2pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66		6,500,000
XVR				
32	SM-XVN1401L2	4CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080PLite & 720P(25fps);The resolution of CH 1 and CH 2 must be the same.So do CH 3 and CH 4 /2CH(Up to 6CH) IP Up to 2MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA/USB2.0*2/P2P/DDNS/ Network RJ45 100Mbps × 1 - Max 10/30 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		19,125,000
33	SM-XVN1801L2	8CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080P Lite/720P: 25fps(PAL)(only CH 1 supports) 1080PLite/720P: 12fps(other channels support) & 720PLite: 25fps /2CH(Up to10CH) IP Up to 5MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA/USB2.0*2/P2P/DDNS/ Network RJ45 100Mbps × 1 - Max 16/60 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		24,625,000

34	SM-XVN11601L2	16CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080P Lite/720P: 25fps(PAL)(only CH 1 supports) 1080PLite/720P: 12fps(other channels support) & 720PLite: 25fps /2CH (Up to18CH) IP Up to 5MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA-CVBS/USB2.0*2/P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/80 Mbps incoming/Outgoing bandwidth Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		40,250,000
35	SM-XVN1401M5	4CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps(PAL)/ 2CH(Up to 6CH) IP Up to 5MP(25fps) H.265 /1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/40 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		26,525,000
36	SM-XVN1801M5	8CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps(PAL)/ 4CH (Up to 12CH) IP Up to 5MP(25fps) H.265 /1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/60 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		42,625,000
37	SM-XVN21608M5	16CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/ 1080P@12fps(PAL) 1080P Lite/720P/WD1@25fps (PAL)/ 8CH (Up to 16CH) IP Up to 5MP/ 25fps (PAL) H.265/HDMI-VGA-CVBS/ Audio IN RCA × 8 - OUT RCA × 1 / Alarm IN 16 CH - OUT4 CH / HDD SATA × 2, E-SATA × 1, up to 10TB Per HDD /RS485 × 1, connect to PTZ or keyboard / USB 2.0 ×1; USB3.0×1 / Power DC12V / 4A Network RJ45 10* 100* 1000Mbps × 1/Bandwidth 32Mbps(Max.64Mbps) Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		94,375,000
38	SM-XVN1401H5	4CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@6fps(only CH 1 support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 2CH (Up to 6CH) IP Up to 8MP(20fps),lower than 8MP @25fps H.265/ 1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/40 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		42,500,000
39	SM-XVN1801H5	8CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps(all channels support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265/ 1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/80 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		73,750,000

40	SM-XVN21601H5	16CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps(half channels support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265/ 1 Audio input - 1 Output /HDD SATA × 2, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 1000Mbps × 1 - Max 32/96 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		137,500,000
41	SM-XVN21608H5	16CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P/WD1 real time preview & Record 4K@8fps(all channels support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P/WD1@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265/Audio IN RCA × 8 - OUT RCA × 1/ Alarm IN 16 CH- OUT 4 CH/ HDD SATA × 2, E-SATA × 1, up to 10TB Per HDD/4K HDMI-VGA-CVBS /RS485 × 1, connect to PTZ or keyboard / USB 2.0 ×1; USB3.0×1/ P2P/DDNS/Network RJ45 1000Mbps × 1 /Bandwidth32Mbps(Max.96Mbps) Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		168,750,000
42	SM-XV43216M5	32CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps(PAL), 1080P Lite/720P/WD1@25fps (PAL)/ 8CH(Up to 24CH) IP Up to 5MP/ 25fps (PAL) /H.265/HDMI-VGA-CVBS/ Audio IN RCA × 16 / OUT RCA × 1 / Alarm IN 16 CH / OUT4 CH /Network RJ45 10* 100*1000Mbps × 1 / Bandwidth 40Mbps(Max.88Mbps) / HDD SATA × 4, E-SATA × 1, up to 10TB Per HDD /RS485 × 1, connect to PTZ or keyboard / USB 2.0 ×1; USB3.0×1 Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		216,250,000
43	SM-XV83216M5	32CH TVI & CVI & AHD- TVI /AHD: 5MP Lite@20fps, 4MP Lite / 1080P / 720P / WD1 real time preview CVI: 4MP Lite / 1080P / 720P / WD1 real time preview /H.265/HDMI-VGA-CVBS/ Record 5MP Lite@10fps,4MP Lite/1080P@12fps(PAL), 1080P Lite/720P/WD1@25fps (PAL)/ 8CH(Up to 24CH) IP Up to 5MP/ 25fps (PAL) Audio IN RCA × 16 / OUT RCA × 1 / Alarm IN 16 CH / OUT4 CH /Network RJ45 10* 100*1000Mbps × 1 /Bandwidth 40Mbps(Max.88Mbps)/ HDD SATA × 8, E-SATA × 1, up to 8TB Per HDD /RS485 × 1, connect to PTZ or keyboard / USB 2.0 × 2 Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		Call
دزدگیر				
44	SM-G6430	مرکز کنترل دزدگیر 4 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار ANDROID و IOS 30 حافظه تلفن (LINE,GSM,SMS) 2 عدد خروجی قابل کنترل با پیام کوتاه و صوتی 24 ساعته و حالت نیمه فعال و دینگ دانگ		46,250,000
45	SM-G6420	مرکز کنترل دزدگیر 5 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار ANDROID و IOS 20 حافظه تلفن (GSM,SMS) 3 عدد خروجی قابل کنترل با پیام کوتاه و صوتی 24 ساعته و حالت نیمه فعال و دینگ دانگ 2 خروجی AUX جهت تغذیه تجهیزات دسترسی آسان به تنظیمات دستگاه از طریق پنل دزدگیر دسترسی به منو از طریق پسورد		42,500,000

46	SM-SG6420	مرکز کنترل دزدگیر 4 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار IOS و ANDROID 20 حافظه تلفن (GSM, SMS) 2 عدد خروجی قابل کنترل با پیام کوتاه و صوتی زون 24 ساعته و حالت نیمه فعال و دینگ دانگ و تأخیری 1 خروجی AUX جهت تغذیه تجهیزات دسترسی آسان به تنظیمات دستگاه از طریق پنل دزدگیر دسترسی به منو از طریق پسورد دارای سیستم هشدار سیگنال مزاحم		40,000,000
47	SM-SD431PR	چشمی دزدگیر باسیم ولتاژ کاری 9 الی 12 ولت 14 متر برد آشکار سازی 90 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت مجهز به ورودی Tamper جریان مصرفی پایین دارای براکت چرخشی جهت نصب در حالت مختلف دارای انتخاب NO , NC		3,125,000
48	SM-SD450PR	چشمی دزدگیر باسیم HLI 968 Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC خروجی آلارم الکترونیکی		4,875,000
49	SM-SD440PR	چشمی دزدگیر باسیم Nicera500 BP Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC - NO خروجی آلارم رله		3,920,000
50	SM-D433WS1	چشمی دزدگیر بیسیم به همراه باتری passive infrared (Nicera500 BP Sensor type) فرکانس کاری 433 مگاهرتز 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی قابلیت تنظیم زون , قابلیت کد دهی , دارای آنتن جهت افزایش برد مازول - دارای کلید تست		5,850,000
51	SM-S103F	آژیر فلاشردار 9 الی 12 ولت 70 دسی بل کمتر از 300 میلی آمپر Sound - Flash		Coming soon
52	اسپیکر دزدگیر	ولتاژ کاری 9 الی 12 ولت دارای پایه برای تنظیم جهت صدای خروجی 25 وات 8 اهم		1,865,000
53	محفظه اسپیکر	محفظه اسپیکر قزی بسیار مقاوم INDOOR / OUTDOOR مقاوم در برابر بارش باران، مقاوم در برابر ضربه، ابعاد مناسب		790,000

کلیه محصولات لیست با گارانتی شرکت سیماران می باشند