

ردیف	سیماران	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
	Datasheet Link	High level -IR		
1	SM-AR512M	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI /3.6mm Fixed lens/ 0.01LUX/20~30m IR 12 VDC/ICR/COC/DWDR, 2DNR,AGC,BLC,AWB,D&N,Sharpness, IP67(Metal&Plastic)		14,500,000
2	SM-D511MV	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI /3.6mm Fixed lens/ 0 lux with IR/ 20~30m IR 12 VDC/ICR/COC/ 2DNR,BLC,AWB,D&N,Sharpness IP66(Metal&Plastic)		14,500,000
3	NEW SM-AR4001	1/2.8" SONY CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens/ 0.001LUX/30m IR/ 12 VDC/ICR/COC/True WDR120DB, Starlight 3DNR,AGC,BLC,AWB,HLC,D&N,Sharpness,Motion Detection,Privacy Mask,SmartIR, Metal IP67		22,500,000
4	NEW SM-IR229	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens / 0.1LUX/18PCS SMD IR-20~30m 12 VDC/ICR/DWDR,2D/3-DNR ,BLC,D&N,AGC,AWB ,UTC Function,Metal IP66		9,850,000
5	NEW SM-D221IRV	1/2.9" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens / 0.1LUX/24PCS IR-20~30m 12 VDC/ICR/DWDR ,2D/3-DNR ,BLC,D&N,AGC,AWB ,UTC Function, Metal IP66		9,450,000
 CV - Warm Light Full Color Camera				
6	SM-AR524MCV	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON)/ 30~35m LED Distance 12 VDC/COC/DWDR, 2DNR,AGC,BLC,AWB,Sharpness,Smart LED, Metal IP67	 	18,000,000
7	SM-D523MCVA	1/2.5" CMOS Sensor/5MP(2560*1936)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON)/ 30~35m LED Distance Support coaxial audio transmission 12 VDC/COC/DWDR, 2DNR,AGC,BLC,AWB,Sharpness,Smart LED, Metal IP67	  	18,500,000

8	SM-AR212MCV	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 20~30m LED Distance 12 VDC/COC/DWDR, 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)	 Full Color	13,750,000
9	SM-D211MCV	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 20~30m LED Distance 12 VDC/COC/DWDR, 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)	 Full Color	13,750,000
10	NEW SM-D211MCVA	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 20m LED Distance/Support coaxial audio transmission 12 VDC/COC/DWDR, 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)	 Full Color	14,500,000
11	SM-D223MCVA	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 30~35m LED Distance/Support coaxial audio transmission 12 VDC/COC/DWDR, 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, Metal IP67	 Full Color	16,750,000
12	NEW SM-CV534	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/4pcs -20m white light view distance/ DC12V/COC/DWDR, 2DNR,BLC,AWB,Smart LED Metal IP66	 Full Color	12,850,000
13	SM-CV133	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,IP 66(Metal&Plastic)	 Full Color	8,800,000
14	SM-CV135	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66	 Full Color	9,500,000
15	SM-CV136	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66	 Full Color	9,550,000
16	SM-CV152	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/4pcs -30~35m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66	 Full Color	13,500,000
17	SM-D120CV	1/2.9" CMOS Sensor/2MP 1080P/720P TVI & AHD & CVI & CVBS/ 3.6mm Fixed lens /0.1LUX/2pcs -20~30m white light view distance/ 12VDC/DWDR,Sharpness,AGC,BLC,3DNR,AWB,UTC,Metal IP66	 Full Color	9,100,000

XVR

18	SM-XVN1401L2	4CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080PLite & 720P(25fps);The resolution of CH 1 and CH 2 must be the same.So do CH 3 and CH 4 /2CH(Up to 6CH) IP Up to 2MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA/USB2.0×2/P2P/DDNS/ Network RJ45 100Mbps × 1 - Max 10/30 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	27,375,000
19	SM-XVN1801L2	8CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080P Lite/720P: 25fps(PAL)(only CH 1 supports) 1080PLite/720P: 12fps(other channels support) & 720PLite: 25fps /2CH(Up to 10CH) IP Up to 5MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA/USB2.0×2/P2P/DDNS/ Network RJ45 100Mbps × 1 - Max 16/60 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	35,000,000
20	SM-XVN11601L2	16CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080P Lite/720P: 25fps(PAL)(only CH 1 supports) 1080PLite/720P: 12fps(other channels support) & 720PLite: 25fps /2CH (Up to 18CH) IP Up to 5MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA-CVBS/USB2.0×2/P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/80 Mbps incoming/Outgoing bandwidth Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	58,500,000
21	SM-XVN1401M5	4CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps(PAL)/ 2CH(Up to 6CH) IP Up to 5MP(25fps) H.265 /1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/40 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	36,000,000
22	SM-XVN1801M5	8CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps(PAL)/ 4CH (Up to 12CH) IP Up to 5MP(25fps) H.265 /1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/60 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WiFi & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	58,000,000

23	 SM-XVN11601M5	16CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MPLite@10fps,4MPLite/ 1080P@12fps, 1080P Lite/720P@25fps / 8CH (Up to 16CH) IP Up to 5MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA × 1, up to 10TB/HDMI-VGA-CVBS/ USB 2.0*2 /RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/80 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	103,750,000
24	SM-XVN21608M5	16CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MPLite@10fps,4MPLite/ 1080P@12fps(PAL) 1080P Lite/720P/WD1@25fps (PAL)/ 8CH (Up to 16CH) IP Up to 5MP/ 25fps (PAL) H.265/HDMI-VGA-CVBS/ Audio IN RCA × 8 - OUT RCA × 1 / Alarm IN 16 CH - OUT 4 CH / HDD SATA × 2, E-SATA × 1, up to 10TB Per HDD /RS485 × 1, connect to PTZ or keyboard / USB 2.0 ×1; USB3.0×1 / Power DC12V / 4A Network RJ45 10* 100* 1000Mbps × 1/Bandwidth 32Mbps(Max.64Mbps) Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	128,750,000
25	 SM-XV43216M5	32CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps / 8CH(Up to 24CH) IP Up to 5MP/ 25fps H.265/16 Audio input - 1 Output/ Alarm IN 16CH - OUT 4CH / HDD SATA × 4, E-SATA × 1, up to 10TB Per HDD / HDMI-VGA-CVBS/ USB 2.0 ×1; USB3.0×1 /RS485 × 1, connect to PTZ or keyboard / P2P/DDNS /Network RJ45 10* 100*1000Mbps × 1 40(Max. 88)/160 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	302,500,000
26	 SM-XV83216M5	32CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps / 8CH(Up to 24CH) IP Up to 5MP/ 25fps H.265/16 Audio input - 1 Output/ Alarm IN 16CH - OUT 4CH / HDD SATA × 8, E-SATA × 1, up to 10TB Per HDD / HDMI-VGA-CVBS/ USB 2.0 ×1; USB3.0×1 /RS485 × 1, connect to PTZ or keyboard / P2P/DDNS /Network RJ45 10* 100*1000Mbps × 1 40(Max. 88)/160 Mbps incoming/Outgoing bandwidth Smart Functions Support coaxial audio-Support USB 3G/4G Dongle قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	352,500,000

27	SM-XVN1401H5	4CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@6fps(only CH 1 support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 2CH (Up to 6CH) IP Up to 8MP(20fps),lower than 8MP @25fps H.265/ 1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/40 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB WIFI & 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	56,250,000
28	SM-XVN1801H5	8CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps(all channels support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265/ 1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/80 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	100,000,000
29	SM-XVN21601H5	16CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps(half channels support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265/ 1 Audio input - 1 Output /HDD SATA × 2, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 1; USB3.0×1 /RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 1000Mbps × 1 - Max 32/96 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	177,500,000
30	SM-XVN21608H5	16CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P/WD1 real time preview & Record 4K@8fps(all channels support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P/WD1@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265/Audio IN RCA × 8 - OUT RCA × 1/ Alarm IN 16 CH- OUT 4 CH/ HDD SATA × 2, E-SATA × 1,up to 10TB Per HDD/4K HDMI-VGA-CVBS /RS485 × 1, connect to PTZ or keyboard / USB 2.0 × 1; USB3.0×1/ P2P/DDNS/Network RJ45 1000Mbps × 1 /Bandwidth32Mbps(Max.96Mbps) Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	222,500,000
درگیر				

31	SM-G6430	مرکز کنترل دزدگیر 4 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار IOS و ANDROID 30 حافظه تلفن (LINE,GSM,SMS) 2 عدد خروجی قابل کنترل با پیام کوتاه و صوتی زون 24 ساعته و حالت نیمه فعال و دینگ دانگ		60,000,000
32	SM-SG6420	مرکز کنترل دزدگیر 4 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار IOS و ANDROID 20 حافظه تلفن (GSM,SMS) 2 عدد خروجی قابل کنترل با پیام کوتاه و صوتی زون 24 ساعته و حالت نیمه فعال و دینگ دانگ و تاخیری 1 خروجی AUX جهت تغذیه تجهیزات دسترسی آسان به تنظیمات دستگاه از طریق پنل دزدگیر دسترسی به منو از طریق پسرورد دارای سیستم هشدار سیگنال مزاحم		46,250,000
33	SM-SD450PR	چشمی دزدگیر باسیم HLI 968 Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC خروجی آلارم الکترونیکی		6,250,000
34	SM-SD440PR	چشمی دزدگیر باسیم Nicera500 BP Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC - NO خروجی آلارم رله		4,950,000
35	SM-D433WS1	چشمی دزدگیر بیسیم به همراه باتری passive infrared (Nicera500 BP Sensor type) فرکانس کاری 433 مگاهرتز 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی قابلیت تنظیم زون , قابلیت کد دهی , دارای آنتن جهت افزایش برد مازول - دارای کلید تست		7,350,000
36	اسپیکر دزدگیر	ولتاژ کاری 9 الی 12 ولت دارای پایه برای تنظیم جهت صدای خروجی 25 وات 8 اهم		2,600,000
37	محفظه اسپیکر	محفظه اسپیکر فلزی بسیار مقاوم INDOOR / OUTDOOR مقاوم در برابر بارش باران، مقاوم در برابر ضربه، ابعاد مناسب		1,050,000

کلیه محصولات لیست با گارانتی شرکت سیماران می باشند