

ردیف	مدل	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
	Datasheet Link	High level -IR		
1	SM-AR828HZ	1/2.5" SONY CMOS Sensor 8MP (3840*2160)@15fps/5MP@20fps/4MP@30fps high resolution TVI/AHD/CVI/CVBS 2.8-12mm motorized lens/ 0.01LUX/50m IR 12VDC/ICR/COC,3DNR,BLC,AWB,D&N,Sharpness,Smart IR, Metal IP67		67,500,000
2	SM-AR822H	1/2.5" SONY CMOS Sensor 8MP (3840*2160)@15fps/5MP@20fps/4MP@30fps high resolution TVI/AHD/CVI/CVBS 3.6mm Fixed lens/ 0.01LUX/30m IR 12VDC/ICR/COC,3DNR,BLC,AWB,D&N,Sharpness,Smart IR, Metal IP67		41,250,000
3	SM-D823HV	1/2.5" SONY CMOS Sensor 8MP (3840*2160)@15fps/5MP@20fps/4MP@30fps high resolution TVI/AHD/CVI/CVBS 2.8mm Fixed lens/ 0.01LUX/30m IR 12VDC/ICR/COC,3DNR,BLC,AWB,D&N,Sharpness,Smart IR, Metal IP67		42,750,000
4	SM-AR512M	1/2.5" CMOS Sensor 5MP (2560*1936)@20fps/4MP@30fps TVI/AHD/CVI 3.6mm Fixed lens/ 0.01LUX/20m IR 12VDC/ICR/COC/DWDR,2DNR,AGC,BLC,AWB,D&N,Sharpness, IP67 (Metal&Plastic)		16,000,000
5	SM-AR512MA	1/2.5" CMOS Sensor 5MP (2560*1936)@20fps/4MP@30fps TVI/AHD/CVI 3.6mm Fixed lens/ 0.01LUX/20m IR 12VDC/ICR/COC/DWDR, 1CH built-in MIC , 2DNR,AGC,BLC,AWB,D&N,Sharpness, IP67 (Metal&Plastic)	 	17,000,000
6	SM-D511MVA	1/2.5" CMOS Sensor 5MP (2560*1936)@20fps/4MP@30fps TVI/AHD/CVI 3.6mm Fixed lens/ 0 lux with IR/ 20m IR 12VDC/ICR/COC, 1CH built-in MIC 2DNR,BLC,AWB,D&N,Sharpness IP66 (Metal&Plastic)	 	17,000,000
7	SM-AR4001	1/2.8" SONY CMOS Sensor 2MP (1920*1080) TVI/AHD/CVI/CVBS 3.6mm Fixed lens/ 0.001LUX/30m IR 12VDC/ICR/COC/ True WDR120DB, Starlight 3DNR,AGC,BLC,AWB,HLC,D&N,LSC,Sharpness, Smart IR,Motion Detection,Privacy Mask Metal IP67		23,500,000
8	SM-D4010ARV	1/2.8" SONY CMOS Sensor 2MP (1920*1080) TVI/AHD/CVI/CVBS 2.8mm Fixed lens/ 0.001LUX/30m IR 12VDC/ICR/COC/ True WDR120DB/ Starlight 3DNR,AGC,BLC,AWB,HLC,D&N,LSC,Sharpness, Smart IR,Motion Detection,Privacy Mask Metal IP67		23,500,000
9	SM-AR212HA	1/2.8" CMOS Sensor 2MP (1920*1080) TVI/AHD/CVI/CVBS 2.8mm Fixed lens/ 0.005LUX/20m IR 12VDC/ICR/COC/DWDR, 1CH built-in MIC 2DNR,AGC,BLC,AWB,HLC,D&N,Sharpness,Smart IR, IP67 (Metal&Plastic)	 	13,700,000

10	SM-D211HVA	1/2.8" CMOS Sensor 2MP(1920*1080) TVI/AHD/CVI/CVBS 2.8mm Fixed lens/ 0.005LUX/20m IR 12VDC/ICR/COC/DWDR,1CH built-in MIC 2DNR,AGC,BLC,AWB,HLC,D&N,Sharpness,Smart IR, IP67(Metal&Plastic)		13,700,000
11	SM-IR348VF	1/2.9" SONY CMOS Sensor 2MP 1080P TVI/AHD/CVI/CVBS 2.8-12 mm VF lens /0.01LUX/30pcs IR-40m 12VDC/ICR/D-WDR,Brightness,Sharpness,Shutter, AGC,BLC,D&N,Defog,3DNR,AWB,UTC,Metal IP66		28,750,000
12	SM-IR229	1/2.9" CMOS Sensor 2MP 1080P/720P TVI/AHD/CVI/CVBS 3.6mm Fixed lens / 0.1LUX/20~30m IR 12VDC/ICR/DWDR,2D/3-DNR ,BLC,D&N,AGC,AWB ,UTC Function,Metal IP66		9,550,000
13	SM-IR219	1/2.9" CMOS Sensor 2MP 1080P/720P TVI/AHD/CVI/CVBS 3.6mm Fixed lens / 0.1LUX/20~30m IR 12VDC/ICR/DWDR,2D/3-DNR ,BLC,D&N,AGC,AWB ,UTC Function,Plastic		8,000,000
14	SM-D222IR	1/2.9" CMOS Sensor 2MP 1080P/720P TVI/AHD/CVI/CVBS 3.6mm Fixed lens / 0.1LUX/20~30m IR 12VDC/ICR/DWDR,2D/3-DNR ,BLC,D&N,AGC,AWB ,UTC Function,Plastic		8,250,000
15	SM-D221IRV	1/2.9" CMOS Sensor 2MP 1080P/720P TVI/AHD/CVI/CVBS 3.6mm Fixed lens / 0.1LUX/20~30m IR 12VDC/ICR/DWDR ,2D/3-DNR,BLC,D&N,AGC,AWB ,UTC Function, Metal IP66		9,350,000
 CV - Warm Light Full Color Camera				
16	SM-AR524MCV	1/2.5" CMOS Sensor 5MP(2560*1936)@20fps/4MP@30fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON)/ 30m LED Distance 12VDC/COC/DWDR,2DNR,AGC,BLC,AWB,Sharpness,S mart LED, Metal IP67		21,000,000
17	SM-D523MCVA	1/2.5" CMOS Sensor 5MP(2560*1936)@20fps/4MP@30fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON)/ 30m LED Distance 12VDC/COC/DWDR,1CH built-in MIC 2DNR,AGC,BLC,AWB,Sharpness,Smart LED, Metal IP67		21,750,000
18	SM-AR512MCVA	1/2.5" CMOS Sensor 5MP(2560*1936)@20fps/4MP@30fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON) / 20m LED Distance 12VDC/COC/DWDR,1CH built-in MIC 2DNR,AGC,BLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)		19,800,000
19	SM-D511MCVA	1/2.5" CMOS Sensor 5MP(2560*1936)@20fps/4MP@30fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens/ 0 lux (LED ON)/ 20m LED Distance 12VDC/COC/DWDR,1CH built-in MIC 2DNR,AGC,BLC,AWB,Sharpness,Smart LED IP67(Metal&Plastic)		19,800,000

20	SM-AR212MCVA	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 20m LED Distance 12VDC/COC/DWDR,1CH built-in MIC 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED IP67(Metal&Plastic)	 Full-Color  	15,800,000
21	SM-D211MCVA	1/2.8" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS- 24/7 full color imaging 2.8mm Fixed lens/ 0 lux (LED ON)/ 20m LED Distance 12VDC/COC/DWDR,1CH built-in MIC 2DNR,AGC,BLC,HLC,AWB,Sharpness,Smart LED, IP67(Metal&Plastic)	 Full-Color  	15,800,000
22	SM-CV552	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color 	17,250,000
23	SM-CV534	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color 	13,500,000
24	SM-CV544	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color 	13,350,000
25	SM-CV537	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color 	13,200,000
26	SM-CV547	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color 	15,000,000
27	SM-D520CV	1/2.5" CMOS Sensor/5MP(2592*1944)@20fps TVI & AHD & CVI - 24/7 full color imaging 3.6mm Fixed lens /0.3LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color 	12,750,000
28	SM-CVM234A	1/2.9" CMOS Sensor/2MP (1920*1080)@25fps TVI & AHD & CVI & CVBS - 24/7 full color imaging 3.6mm Fixed lens /0.1LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED, Metal IP66	 Full-Color  	12,050,000
29	SM-CVM237A	1/2.9" CMOS Sensor/2MP (1920*1080)@25fps TVI & AHD & CVI & CVBS - 24/7 full color imaging 3.6mm Fixed lens /0.1LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED Metal IP66	 Full-Color  	12,000,000

30	SM-D220CVMA	1/2.9" CMOS Sensor/2MP (1920*1080)@25fps TVI & AHD & CVI & CVBS - 24/7 full color imaging 3.6mm Fixed lens /0.1LUX/20~30m white light view distance DC12V/COC/DWDR,2DNR,BLC,AWB,Smart LED, Metal IP66		11,500,000
31	NEW SM-CV252FA	1/3" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS 3.6mm Fixed lens / 0.01LUX/30m white light view distance 12VDC/DWDR,1CH built-in MIC BLC,2DNR,AWB,Smart IR,UTC, Metal IP66		14,000,000
32	NEW SM-CV234FA	1/3" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS 3.6mm Fixed lens / 0.01LUX/20~30m white light view distance 12VDC/DWDR,1CH built-in MIC BLC,2DNR,AWB,Smart IR,UTC, Metal IP66		9,800,000
33	NEW SM-CV237FA	1/3" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS 3.6mm Fixed lens / 0.01LUX/20~30m white light view distance 12VDC/DWDR,1CH built-in MIC BLC,2DNR,AWB,Smart IR,UTC, Metal IP66		9,750,000
34	NEW SM-D220CVFA	1/3" CMOS Sensor/2MP(1920*1080) TVI & AHD & CVI & CVBS 3.6mm Fixed lens / 0.01LUX/20~30m white light view distance 12VDC/DWDR,1CH built-in MIC BLC,2DNR,AWB,Smart IR,UTC,Metal IP66		9,100,000
XVR				
35	SM-XVS1401L2	4CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080P Lite & 720P(25fps) /2CH(Up to 6CH) IP Up to 2MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA/USB2.0*2/P2P/DDNS/ Network RJ45 100Mbps × 1 - Max 10/30 Mbps incoming/Outgoing bandwidth Support coaxial audio Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		26,250,000
36	SM-XVS1801L2	8CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080P Lite/720P: 25fps(PAL)(only CH 1 supports) 1080P Lite/720P: 12fps(other channels support) & 720P Lite: 25fps /2CH(Up to10CH) IP Up to 5MP(25fps) H.265/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA/USB2.0*2/P2P/DDNS/ Network RJ45 100Mbps × 1 - Max 16/60 Mbps incoming/Outgoing bandwidth Support coaxial audio Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی		32,250,000

37	SM-XVN11601L2-V2	16CH TVI&AHD&CVI 2MP Live(25fps) & Record 1080P Lite/720P: 25fps(PAL)(only CH 1 supports) 1080P Lite/720P: 12fps(other channels support) & 720P Lite: 25fps /2CH (Up to18CH) IP Up to 5MP(25fps) H.265+/1 Audio input - 1 Output/ HDD SATA×1, up to 8TB/HDMI-VGA-CVBS/ USB2.0*2/P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/80 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	58,000,000
38	SM-XVN1401M5-AI	4CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps(PAL)/ 2CH(Up to 6CH) IP Up to 5MP(25fps) H.265+ /1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/40 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 4CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	40,500,000
39	SM-XVN1801M5-AI	8CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps(PAL)/ 4CH (Up to 12CH) IP Up to 5MP(25fps) H.265+ /1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/60 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 8CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	64,000,000
40	SM-XVN11601M5-AI	16CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/ 1080P@12fps, 1080P Lite/720P@25fps / 8CH (Up to 16CH) IP Up to 5MP(25fps) H.265+/1 Audio input - 1 Output/ HDD SATA × 1, up to 10TB/HDMI-VGA-CVBS/ USB 2.0*2 /RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/80 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 16CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	125,000,000

41	SM-XVN21608M5-AI	16CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps(PAL) 1080P Lite/720P@25fps (PAL)/ 8CH (Up to 16CH) IP Up to 5MP/ 25fps (PAL) H.265+/HDMI-VGA-CVBS/ Audio IN RCA × 8 - OUT RCA × 1 / Alarm IN 16 CH - OUT 4 CH / SATA × 2, E-SATA × 1, up to 10TB Per HDD/ RS485 × 1, connect to PTZ or keyboard / USB 2.0 ×1; USB3.0×1 / Power DC12V / 4A Network RJ45 10* 100* 1000Mbps × 1/Bandwidth 32Mbps(Max.64Mbps) Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 16CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	158,000,000
42	SM-XV43216M5	32CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps / 8CH(Up to 24CH) IP Up to 5MP/ 25fps H.265/16 Audio input - 1 Output/ Alarm IN 16CH - OUT 4CH / SATA × 4, E-SATA × 1, up to 10TB Per HDD / HDMI-VGA-CVBS/ USB 2.0 ×1; USB3.0×1 /RS485 × 2, connect to PTZ or keyboard / P2P/DDNS /Network RJ45 10* 100*1000Mbps × 1 40(Max. 88)/160 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	350,000,000
43	SM-XVN43216M5-AI	32CH TVI&AHD&CVI: 5MP Lite@20fps, 4MP Lite / 1080P / 720P real time preview & Record 5MP Lite@10fps,4MP Lite/1080P@12fps, 1080P Lite/720P@25fps / 8CH(Up to 24CH) IP Up to 5MP/ 25fps H.265+/16 Audio input - 1 Output/ Alarm IN 16CH - OUT 4CH / SATA × 4, E-SATA × 1, up to 10TB Per HDD / HDMI-VGA-CVBS/ USB 2.0 ×1; USB3.0×1 /RS485 × 2, connect to PTZ or keyboard / P2P/DDNS /Network RJ45 10* 100*1000Mbps × 1 40(Max. 88)/160 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 16CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	370,000,000
44	SM-XVN1401H4K-AI	4CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps, 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 2CH (Up to 6CH) IP Up to 8MP(20fps),lower than 8MP @25fps H.265+/ 1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 16/40 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 4CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	69,250,000

45	SM-XVN1801H4K-AI	8CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps, 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 8CH (Up to 16CH) IP Up to 8MP(25fps) H.265+ / 1 Audio input - 1 Output /HDD SATA × 1, up to 10TB/ 4K HDMI-VGA-CVBS/USB 2.0 × 2/ RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 100Mbps × 1 - Max 32/80 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 8CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	122,750,000
46	SM-XVN21601H4K-AI	16CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps, 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265+ / 1 Audio input - 1 Output /HDD SATA × 2, up to 10TB/ 4K HDMI-VGA-CVBS/USB 3.0 × 1; USB2.0 × 1 /RS485 × 1, connect to PTZ or keyboard / P2P/DDNS/Network RJ45 1000Mbps × 1 - Max 32/96 Mbps incoming/Outgoing bandwidth Support coaxial audio-Support USB 3G/4G Dongle Smart Functions(IPC) AI Functions(Analog : 16CH SMD,1CH Perimeter) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	  	223,750,000
47	SM-XVN21608H5	16CH TVI&AHD&CVI : 4K@15fps, 5MP@20fps, 4MP/3MP/1080P/720P real time preview & Record 4K@8fps(all channels support), 4K Lite@12fps, 5MP@12fps, 5MP Lite@20fps, 4MP/3MP@12fps, 4MP Lite/1080P/720P@25fps/ 8CH(Up to 16CH) IP Up to 8MP(25fps) H.265/Audio IN RCA × 8 - OUT RCA × 1/ Alarm IN 16 CH- OUT 4 CH/ SATA × 2, E-SATA × 1, up to 10TB Per HDD/4K HDMI-VGA-CVBS /RS485 × 1, connect to PTZ or keyboard / USB 2.0 ×1; USB3.0×1/ P2P/DDNS/Network RJ45 1000Mbps × 1 /Bandwidth32Mbps(Max.96Mbps) Support coaxial audio-Support USB 3G/4G Dongle Smart Functions قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	 	275,000,000
دزدگیر				
48	SM-G6430	مرکز کنترل دزدگیر 4 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار IOS و ANDROID 30 حافظه تلفن (LINE,GSM,SMS) 2 عدد خروجی قابل کنترل با پیام کوتاه و صوتی زون 24 ساعته و حالت نیمه فعال و دینگ دانگ		79,000,000
49	SM-SG6420	مرکز کنترل دزدگیر 4 زون با سیم + 1 زون بی سیم (با قابلیت گسترش) کنترل دستگاه از طریق تماس، پیامک و نرم افزار IOS و ANDROID 20 حافظه تلفن (GSM,SMS) 2 عدد خروجی قابل کنترل با پیام کوتاه و صوتی زون 24 ساعته و حالت نیمه فعال و دینگ دانگ و تاخیری 1 خروجی AUX جهت تغذیه تجهیزات دسترسی آسان به تنظیمات دستگاه از طریق پنل دزدگیر دسترسی به منو از طریق پسورد دارای سیستم هشدار سیگنال مزاحم		56,625,000

50	SM-SD450PR	چشمی دزدگیر باسیم HLI 968 Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC خروجی آلارم الکترونیکی		7,500,000
51	SM-SD440PR	چشمی دزدگیر باسیم Nicera500 BP Sensor type ولتاژ کاری 9 الی 15 ولت 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی passive infrared دارای قابلیت تنظیم میزان حساسیت قابلیت تنظیم LED بصورت ON/OFF مجهز به ورودی Tamper دارای انتخاب NC - NO خروجی آلارم رله		5,750,000
52	SM-D433WS1	چشمی دزدگیر بیسیم به همراه باتری passive infrared (Nicera500 BP Sensor type) فرکانس کاری 433 مگاهرتز 14 متر برد آشکار سازی 140 درجه زاویه آشکار سازی قابلیت تنظیم زون , قابلیت کد دهی , دارای آنتن جهت افزایش برد مژول - دارای کلید تست		8,250,000
53	اسپیکر دزدگیر	ولتاژ کاری 9 الی 12 ولت دارای پایه برای تنظیم جهت صدای خروجی 25 وات 8 اهم		3,250,000
54	محفظه اسپیکر	محفظه اسپیکر فلزی بسیار مقاوم INDOOR / OUTDOOR مقاوم در برابر بارش باران، مقاوم در برابر ضربه، ابعاد مناسب		1,225,000

کلیه محصولات لیست با گارانتی شرکت سیماران می باشند

